## **SPLIT**

SPECIFICATIONS		
MOUNTING		WALL RECESSED
POWER	[W]	2
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	185
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	-
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	92

220-240V AC 50/60 Hz POWER SUPPLY [V] [A] LED-DRIVER **INCLUDED DIMMING** NO THROUGH-WIRING NO


MATERIAL **ALUMINUM INGRESS PROTECTION** IP20 PROTECTION CLASS Ш **NET WEIGHT** 0,67 [kg] **GROSS WEIGHT** [kg] 0,70

COLOUR (HOUSING) WHITE ~RAL9003 / WHITE COLOUR (HOUSING) WHITE ~RAL9003 / GOLD

CUT-OUT (FIXTURE) 25x164 [mm] CUT-OUT (MOUNT. BOX) 84x260 [mm] RECESSED DEPTH 55 (MOUNTING BOX) [mm] RECESSED DEPTH 45 (FIXTURE) [mm]

\*Luminous flux values are nominal LED data at a operating temperature of 25° C







## **OPTIONS / OPTIONAL ACCESSORIES**




## **CUT OUT DIMENSIONS**

## FIXTURE DIMENSIONS















IP20

**DLS LIGHTING** 

www.dlslighting.com

