



stic spike connect Design: Klaus Nolting



stic spike connect Design: Klaus Nolting

für unbefestigte Beet- und Grünflächen for unpaved beds and greens

Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: Flood

Anschluss:
5 m Zuleitung
(H05RN8-F 3G0,75 mm²)
inkl. connect Stecker
5 m Zuleitung auf Anfrage
kürzbar

ortsveränderlich

Material:
Kopf: Aluminiumguss
pulverbeschichtet
Stab: Edelstahl
pulverbeschichtet
Sicherheitsglas klar

Schutzart:
IP65



Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

reflector: flood

connection:
5 m supply cable
(H05RN8-F 3G0,75 mm²)
incl. connect plug 5 m supply
cable can be shortened
on request

movable

material:
head: aluminium die-casting
powder-coated
pole: stainless steel
powder-coated
glass: safety glass clear


protection class:
IP65



light direction:



stic 30 spike




anthracite
RAL 7016 91061-27-AN-CO **8 W/559 lm**

cool brown 91061-27-CB-CO **8 W/559 lm**

deep black
RAL 9005 91061-27-BL-CO **8 W/559 lm**

stic 70 spike



anthracite
RAL 7016 91060-27-AN-CO **8 W/559 lm**

cool brown 91060-27-CB-CO **8 W/559 lm**

deep black
RAL 9005 91060-27-BL-CO **8 W/559 lm**

Größe in mm
size in mm